

Electrical specification

DC resistance:  
 Total primary: 411.0 ohms +/- 15%  
 Total secondary: 0.9 ohms +/- 15%

Primary impedance: 8k centre tapped

Inductance measured at 1kHz, 0.27V:  
 Primary: (10 - 6): 12.0H min.  
 Secondary: (12 - 13): 26.7mH min.  
 (12 - 14): 57.0mH min.


Isolation: primary to secondary: 500V DC min.  
 Frequency range: 50Hz - 20kHz +/- 3dB

Suitable for use with push-pull valve amplifiers e.g. valve type EL84.  
 Manufactured with grain orientated silicon steel laminations for reduced hum, low distortion, low insertion loss and stray field.

Tolerance on all dimensions +/- 1mm unless stated otherwise



Unit 5, Oxonian Park, Langford Locks,  
 Kidlington, Oxfordshire. OX5 1FP  
 Tel: (01865) 855085 Fax: (01865) 855075  
 Website: [www.oep.co.uk](http://www.oep.co.uk)

DESCRIPTION	ISSUE	DATE	DRAWN	CHECKED	DRAWING NUMBER
15W audio matching transformer 8k C.T. to 0 - 8 - 16 ohms 	1	20/03/03	CS		<b>N35A004F</b>
	2	07/03/06	CS		
	3	05/08/15	CS		
	4	20/08/18	CS		

Scale: nts All dimensions in mm unless stated otherwise